



POWERPLUS

SOLAR & GENERATOR

Warehouse Racking Systems \ Mezzanine Floors \ Generators & Compressors

PP Perkins 220

Prime Power Generator Three Phase

Specifications

Alternator

Make	Stamford/Leroy Somer
Model	UCI274H/TAL046B
Frequency	50Hz & 1500rpm
Output Continuous / Standby	200/220 KVA
Rotating Speed	1500RPM
No. of Phases	Three Phase 12 wires
Rated Voltage	380/415
Power Factor	0.8

Engine

Make & Model	Perkins 1106A - 70TAG4
Type	Mechanical
Output Rating	380-415 V, 3 ph, 50Hz, 1500rpm 200-220KVA/160-176KW
No. of Cylinders-Bore X Stroke	6-(105 x 135mm)
Piston Displacement	7.01L
Fuel	Diesel
Fuel Consumption	23.1 L/H @50% load L/H 34.7 L/H @75% load L/H 45.8 - 49.4 L/H @100% load L/H
Lube Oil Sump Cap	16.5L
Coolant Capacity	21L
Battery Capacity	12 - 100x2pc
Fuel Tank Capacity	350L
Cooling System	Water - Cooled
Cycle	4 Stroke
Combustion System	Direct Injection
Compression Ratio	16:1
Rotation	Anti-clockwise
Exhaust Temperature °C	550
Gross Engine Power	178.9KW(240hp) - 196.3KW (263hp)

Unit

Dimensions (L/W/H cm)	211x 69x 130
Wet Weight	1697kg

Control Panel

Make	Deep Sea
Model	4000 Series



Alternator

INSULATION SYSTEM

- The insulation system is class H.
- All windings are impregnated in either a triple dip themorsetting liquid, oil and acid resisiting polyester varnish or vacuum pressure impregnated with a special polyester resin.
- Heavy coat of antitracking varnish additional protection against moisture or condensation

AUTOMATIC VOLTAGE REGULATOR (AVR)

The fully sealed automatic voltage regulator maintains the voltage regulation at $\pm 1\%$. Nominal adjustment by means of a trim pot incorporated on the AVR.

MOTOR STARTING

An overload capacity equivalent to 300% of the Full Load impedance at zero Power Factor can be sustained for 10 seconds, when AREP or PMG option is fitted.

Mounting Arrangement

BASE FRAME

The complete Generating Set is mounted as a whole on a heavy duty fabricated steel Baseframe.

COUPLING

The Engine and Alternator are directly coupled by means of an SAE flange. The Engine flywheel is flexibly coupled to the Alternator rotor.

ANTI-VIBRATION MOUNTING PADS

Anti-Vibration pads are affixed between the Engine / Alternator feet and the baseframe thus ensuring complete vibration isolation of the rotating assembly.

SAFETY GUARDS

The Fan & Fan Drive along with the battery Charging Alternator are safety Guard protected for personnel protection

Engine / Engine Filtration System

Perkins four stroke heavy duty high performance industrial type diesel engine.

- Cartridge type dry air filter.
- Two Cartridge type fuel filter.
- Full flow lube oil filter.

All filters have replaceable elements.