



POWERPLUS
SOLAR & GENERATOR

Warehouse Racking Systems \ Mezzanine Floors \ Generators & Compressors

PC Cummins 500

Prime Power Generator Three Phase

Specifications

Alternator

Make	Stamford / Leroy Somer
Model	HCI634G1 / TAL047C
Frequency	50Hz & 1500rpm
Output Continuous / Standby	500/550 KVA
Rotating Speed	1500RPM
No. of Phases	Three Phase 12 wires
Rated Voltage	380/415
Power Factor	0.8

Engine

Make & Model	QSZ13-G3
Type	4 cycle, in-line, Turbo charged
Output Rating	380-415 V, 3 ph, 50Hz, 1500rpm 500-550KVA/400-440KWe
No. of Cylinders-Bore X Stroke	6-(159 x 159mm)
Piston Displacement	18.9L
Fuel	Diesel
Fuel Consumption	57L/H @50% load L/H 82L/H @75% load L/H 107L/H @100% load L/H
Lube Oil Sump Cap	150L
Coolant Capacity	95L
Battery Capacity	24V - 125x2pc
Fuel Tank Capacity	410L
Cooling System	Jacket Water After Cooled
Cycle	4 Stroke
Combustion System	Direct Injection Cummins PT
Compression Ratio	16.1:1
Rotation	Anti-clockwise
Exhaust Temperature °C	55
Gross Engine Power	366kWm - 407kWm

Unit

Dimensions (L/W/H cm)	336x 117x 203
Wet Weight	2250kg

Control Panel

Make	Deep Sea
Model	7000 Series



Alternator

INSULATION SYSTEM

- The insulation system is class H.
- All windings are impregnated in either a triple dip themorsetting liquid, oil and acid resisiting polyster varnish or vacuum pressure impregnated with a special polyster resin.
- Heavy coat of antitracking varnish additional protection against moisture or condensation

AUTOMATIC VOLTAGE REGULATOR (AVR)

The fully sealed automatic voltage regulator maintains the voltage regulation at $\pm 1\%$. Nominal adjustment by means of a trim pot incorporated on the AVR.

MOTOR STARTING

An overload capacity equivalent to 300% of the Full Load impedance at zero Power Factor can be sustained for 10 seconds, when AREP or PMG option is fitted.

Mounting Arrangement

BASE FRAME

The complete Generating Set is mounted as a whole on a heavy duty fabricated steel Baseframe.

COUPLING

The Engine and Alternator are directly coupled by means of an SAE flange. The Engine flywheel is flexibly coupled to the Alternator rotor.

ANTI-VIBRATION MOUNTING PADS

Anti-Vibration pads are affixed between the Engine / Alternator feet and the baseframe thus ensuring complete vibration isolation of the rotating assembly.

SAFETY GUARDS

The Fan & Fan Drive along with the battery Charging Alternator are safety Guard protected for personnel protection

Engine / Engine Filtration System

Cummins four stroke heavy duty high performance industrial type diesel engine.

- Cartridge type dry air filter.
- Two Cartridge type fuel filter.
- Full flow lube oil filter.

All filters have replaceable elements.